



SPTK-09A

High Precision Fiber Cleaver



Features

- Precise cleaved surfaces; Smooth cleaving angle around 0.5 degree
- Blade lifetime up to 2000 times each point, 24 cutting point, blade life time up to 48000times;
- Automatic return of blade, one step to finish; convenient design, easy to use;
- Smart design of pressure pads preventing the fiber from damage by the return of blade carriage
- Easy-step operation to complete the cleaving and collection of waste fiber shards.
- Main Body is aluminum material; Blade magnesium alloy materials

Specification

Model	SPTK-09A
Cleave Angle	≤0.5°
Cleave Length	0.25mm fiber:9~16mm 0.9mm fiber:10~16mm
Fiber Diameter	125μm
Coating Diameter	0.25&0.9mm
Size	63W×56D×56H(mm)



Weight	280g
Blade Life Time	Around 48000 fibers
Blade Point	24 point
Scrap Collector Bin	Yes
Operating Temp.	-40-80 °C

Precision Sharp Cleaver Blade



Product Name	Replacement Blade
Outer Diameter	20mm
Inner Diameter	4mm
Thickness	3mm
Material of Blade	Tungsten Steel
Blade Cutting Point	24
Life Span of Each cut point	2000~2500times
Life span of Blade	48000~60000times

Ordering information

Part Number	Product Description
SPTK-09A	High Precision Fiber Cleaver type A

Note: If you need more customized services, please contact us.

E-mail: info@sopto.com.cn

Web : <http://www.sopto.com.cn>