

4G LTE Router With Detachable 4G Antennas

MW5360



OVERVIEW:

The Netis 4G LTE router MW5360 is equipped with a 4G LTE module, which allows you to access the Internet with a SIM card. With the separate WiFi antenna systems and unique detachable 4G antenna ports design, it allows you to put the 4G antennas anywhere inside or outside of your house, which brings you a better 4G speed and better WiFi performance. MW5360 also offers a wired WAN port to be used as a common wireless router.

FEATURES:

- Plug & play, access the internet without any setting
- Wide Band for LTE, fit for most ISPs
- Multi-access, 4G LTE and Wired access available
- Works seamlessly with all 802.11a/b/g/n devices
- Simultaneous 2.4GHz 300Mbps
- 2* 5dBi high gain WiFi antennas and 2*5dBi detachable 4G antennas

- Easy wireless security setup at a push of the WPS button
- Intelligent bandwidth control to manage the bandwidth usage for each computer reasonably
- Internet Access Control- IP filtering, MAC Filtering, Domain Filtering based on time
- Quick setup, with built-in multilingual management page

SPECIFICATION:

Wireless	
Standards	IEEE 802.11b/g/n 2.4GHz
Signal Rate	Up to 300Mbps2.4GHz
Frequency Range	2.4-2.4835GHz;5.180-5.825GHZ
Transmit Power	20dBm(MAX)
	802.11n: 40MHz(300Mbps, 270Mbps, 240Mbps, 180Mbps, 120Mbps, 90Mbps, 60Mbps, 30Mbps) 20MHz (144Mbps, 130Mbps, 115Mbps, 86Mbps, 57Mbps, 43Mbps, 28Mbps, 14Mbps) (Auto-Sense)
	801.11g: (54Mbps, 48Mbps, 36Mbps, 24Mbps, 18Mbps, 12Mbps, 11Mbps, 9Mbps, 6Mbps)
	802.11b: (11Mbps,9Mbps, 6Mbps, 5.5Mbps, 2Mbps, 1Mbps)
Wireless Modes	AP/APR, Multi-SSID
Wireless Security	None / WEP / WPA-PSK / WPA2-PSK / WPA2-Mixed/WPS
4G LTE	
Band for LTE	FDD-LTE:B1/B3/B5/B8 TDD-LTE: B38/B39/B40/B41 HSPA/UMTS:B1/B5/B8 GSM/GPRS/EDGE:B3/B8 TD-SCDMA:B34/B39 EVDO/CDMA:BC0
Mode	FDD-LTE、TDD-LTE、TD-SCDMA、HSPA+、HSUPA HSDPA、UMTS、EVDO、EDGE、GPRS、GSM、CDMA1x
Card Speed	FDD-LTE: 150 Mbps DL, 50 Mbps UL TDD-LTE: 132 Mbps DL, 30 Mbps UL TD-HSUPA:2.8Mbps DL TD-HSUPA:2.2Mbps UL DC-HSPA+:42 Mbps DL HSPA+:21 Mbps DL HSUPA:5.76Mbps UL WCDMA: 384 Kbps DL, 384Kbps UL CDMA2000 EVDO: 3.1Mbps DL, 1.8Mbps UL EDGE: 237 Kbps DL, 118Kbps UL

	GPRS:85.6 Kbps DL, 85.6 Kbps UL
Hardware	
Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX
Interface	1*10/100Mbps Auto MDI/MDIX RJ45 WAN port
	2*10/100Mbps Auto MDI/MDIX RJ45 LAN port
	SIM card slot
LED Indicators	Power, LAN All, WiFi/WPS,EWAN, LTE Strong, LTE Middle, LTE Weak
Buttons	Default, WPS
Antenna	2* 5dBi WiFi antennas, 2 SMA detachable 4G antennas
Power Supply	DC 12V/1.0A(Output)
Dimensions (L x W x H)	182mm*108mm*25mm
WAN Type	WAN: DHCP / Static IP / PPPoE / Russia PPPoE / L2TP / PPTP / 3G&4G
Others	Bandwidth Control, Access Control, IPTV, Virtual Server, DMZ,
	VPN Pass-through, Dynamic DNS, Static Routing
Others	
Certification	FCC, CE, EAC
Environment	Operating Temperature: 0°C~40°C
	Storage Temperature: -40°C~70°C
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing
Package	1* MW3560
	1* 12V/1.0A Power Adapter
	1* Quick Installation Guide (Multilingual)

PICTURES:

